



THE HARRIS PRODUCTS GROUP
A LINCOLN ELECTRIC COMPANY
4501 Quality Place • Mason, OH 45040 U.S.A Tel: 513-754-2000 Fax: 513-754-6015
C/Arq Ricard Giralt s/n • Figueres, E-17600 SPAIN
Tel: +34-972-678-826 Fax: +34 972 505 143
TECHNICAL SPECIFICATION SHEET

Harris L-Ag5 BRAZING FILLER METAL

NOMINAL CHEMICAL COMPOSITION:

Ag %	Cu %	Zn %	Si %	Others %
5,0 – 6,0	54,0 – 56,0	38,0 – 42,0	0,05 – 0,25	0,15

PHYSICAL AND MECHANICAL PROPERTIES:

Tensile strength (N/mm ²)	Specific Weight (gr/cm ³)	Working Temperature (°C)	Melting range (°C)	Joint clearance (MM)
350	8,4	860	820 – 870	0,05 – 0,13

BRAZING PROPERTIES:

L-Ag5 filler metal is an economical alloy with large melting range. The wetting and flow characteristics make L-Ag5 an appropriate choice to join brass and iron connections. Colour Brass.

AVAILABLE FORMS:

Standard wire diameters (rods, coils and spools), preformed rings, bend returns on different length and sizes.

SPECIFICATION COMPLIANCE:

ISO 17672	Ag- 205
DIN EN1044	Ag- 208
DIN8513	L-Ag5
AWS A5.8	-
NFA 81-362	05A1
BS 1845	-

RECOMMENDED FLUX:

Always is necessary use 600 bronze brazing flux.

APPLICATIONS:

L-Ag5 is especially used on iron piping connections, where fine appearance has to be shown.

WARNING: PROTECT yourself and others. Read and understand this information.

FUMES AND GASES can be hazardous to your health.

- Before use, read and understand the material Safety Data Sheets (MSDS), and your employer's safety practices.
- Keep your head out of fumes.
- Use enough ventilation, exhaust at the arc, or both, to keep fumes and gases from your breathing zone and the general area.
- Wear correct eye, ear, and body protection.

All statements, information and data given are believed to be accurate and reliable but are presented without guarantee, warranty or responsibility of any kind, expressed or implied. Additional information available at our web site: www.harrisproductsgroup.com ISO 9001.